


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H01J 29/76	A1	(11) International Publication Number: WO 00/57448
		(43) International Publication Date: 28 September 2000 (28.09.00)
(21) International Application Number: PCT/EP00/02598	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 23 March 2000 (23.03.00)		
(30) Priority Data: 99/03655 24 March 1999 (24.03.99) FR		
(71) Applicant (for all designated States except US): THOMSON TUBES & DISPLAYS S.A. [FR/FR]; 46, quai Alphonse Le Gallo, F-92100 Boulogne-Billancourt (FR).		
(72) Inventors; and	Published <i>With international search report.</i>	
(75) Inventors/Applicants (for US only): AZZI, Nacerdine [FR/FR]; Thomson Multimedia, 46, quai Alphonse Le Gallo, F-92648 Boulogne Cedex (FR). MASSON, Olivier [FR/FR]; Thomson Multimedia, 46, quai Alphonse Le Gallo, F-92648 Boulogne Cedex (FR). VOLATIER, Sébastien [FR/FR]; Thomson Multimedia, 46, quai Alphonse Le Gallo, F-92648 Boulogne Cedex (FR).		
(74) Agent: MOJAL, Gérard; Thomson Multimedia, 46, quai Alphonse Le Gallo, F-92648 Boulogne Cedex (FR).		

(54) Title: DEFLECTION UNIT FOR SELF-CONVERGING CATHODE-RAY TUBES WITH REDUCED TRAPEZOID DIFFERENTIAL



(57) Abstract

Electromagnetic deflection unit for colour cathode-ray tubes, comprising a pair of frame deflection coils and a pair of line deflection coils, at least one of these two pairs of coils having the shape of a saddle, each saddle-shaped deflection coil (3) having a rear bundle (19) placed on the side facing the electron gun and a front bundle (29) on the side facing the screen, two lateral harnesses of conductors connecting the front bundle to the rear bundle, each lateral harness being characterized in that the external edge of the said lateral harness lies in a radial angular position close to 0° at the rear of the coil and in a radial angular position greater than 5° at the front of the coil, so as to minimize the trapezoid differential error between the red and blue beams.